



Test Report : DPB09A-12

9W SIP Package DC-DC Regulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.5 % ~ +1.5 % (Max)	I/P:12VDC O/P:FULL LOAD Ta:25°C	12.052 +0.43% -12.058 +0.48%	P
2	RIPPLE & NOISE	100 mVp-p (Max)	I/P:12VDC O/P:FULL LOAD Ta:25°C	42mV 50mV	P
3	LINE REGULATION	-0.5% ~ +0.5% (Max)	I/P:9VDC~18VDC O/P:FULL LOAD Ta:25°C	12.070 12.052 12.057 +0.14% ~ +0.04% -12.078 -12.058 -12.060 +0.16% ~ +0.02%	P
4	LOAD REGULATION	-0.5% ~ +0.5% (Max)	I/P:12VDC O/P:10% LOAD~FULL LOAD Ta:25°C	12.052 12.054 12.059 -0.02% ~ +0.04% -12.058 -12.061 -12.066 +0.02% ~ +0.04%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	9 VDC ~18 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.64VDC ~18.0 VDC	P
2	EFFICIENCY	88% (Typ)	I/P:12VDC O/P:FULL LOAD Ta:25°C	88.1%	P
3	DC CURRENT	862 mA / FULL LOAD (Max) 22 mA / NO LOAD (Max)	I/P:12VDC O/P:NO / FULL LOAD Ta:25°C	845 mA / FULL LOAD 19.38 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	CONTINUOUS	I/P:18VDC O/P:FULL LOAD Ta:25°C	HICCUP MODE AUTO-RECOVER	P
2	OVER LOAD PROTECTION	120% ~ 250% (Typ)	I/P:12VDC O/P:TESTING Ta:25°C	150.5% HICCUP MODE AUTO-RECOVER	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C. ~ - Vin>2.5V or open circuit Power off : R.C. ~ - Vin <0.8Vdc or short	I/P:12VDC O/P:FULL LOAD Ta:25°C	Power on : R.C>2.5Vdc or Open Power off : R.C<0.8Vdc	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1.5K VDC/min	I/P-O/P:1.5K VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>1000MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>1000MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT												
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 8HRS I/P:12VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 8HRS I/P:12VDC O/P:FULL LOAD Ta=60°C 3. HIGH AMBIENT BURN-IN : 8HRS I/P:12VDC O/P:55% LOAD Ta=80°C 4. HIGH AMBIENT BURN-IN : 8HRS I/P:12VDC O/P:40% LOAD Ta=90°C			P												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>66.0°C</td> <td>97.9°C</td> <td>99.6°C</td> <td>106.7°C</td> </tr> </tbody> </table>				NO	Position	1	2	3	4	1	CASE	66.0°C	97.9°C	99.6°C	106.7°C
NO	Position	1	2	3	4												
1	CASE	66.0°C	97.9°C	99.6°C	106.7°C												
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:12VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P												

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 3.75905 M.T.B.F : 266,024.80 HRS			P
TEST RESULT		TESTER		APPROVAL	
PASS		ARCHEN HSIAO		PETER CHENG	