



Test Report: IDPC-25-350

25W Constant Current Mode LED Driver

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST



NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CONSTANT CURRENT REGION	49V~70V	I/P: 230VAC O/P: LED MODE Ta: 25°C	14V~70V
2	CURRENT RIPPLE	5% max@rated current	I/P: 230VAC O/P: FULL/MIN LOAD Ta: 25°C	2.5%
3	CURRENT TOLERANCE	±7%	I/P: 230VAC O/P: FULL/MIN LOAD Ta: 25°C	4.2%
4	OPEN CIRCUIT VOLTAGE (max)	100V	I/P: 230VAC O/P: NO LOAD Ta: 25°C	73.47V
5	OVER/UNDERSHOOT TEST	<±5 %	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	±1.173%
6	SET UP TIME	500ms/230VAC 1200ms/115VAC	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	404ms/230VAC 336ms/115VAC
<p>INPUT=230VAC/50HZ @ FULL LOAD</p> <p>CH1: Output Voltage CH2: AC Input Voltage</p> <p>Δ: 275 V @: 0.00 V Δ: 404ms @: -386ms</p> <p>Ch1 14.0 V Ch2 250 V 100ms A Ch1 56.0 V</p>		<p>INPUT=115VAC/60HZ @ FULL LOAD</p> <p>CH1: Output Voltage CH2: AC Input Voltage</p> <p>Δ: 120 V @: 0.00 V Δ: 336ms @: -320ms</p> <p>Ch1 14.0 V Ch2 250 V 100ms A Ch1 56.0 V</p>		
7	AUXILIARY DC OUTPUT (For A-Type only)	Nominal 12V (deviation 11.4~12.6) @50mA	I/P: 230 VAC O/P: FULL LOAD	11.990 V

8 DIMMING TEST



SPEC:

- Output constant current level can be adjusted by applying one of the two methodologies between DIM+ and DIM-: 0 ~ 10Vdc, or 10V PWM signal.
- Direct connecting to LEDs is suggested. It is not suitable to be used with additional drivers.

© Applying additive 0 ~ 10VDC



© Applying additive 10V PWM signal (frequency range 300Hz ~ 3KHz):



- Note : 1. Min. dimming level is about 8% and the output current is not defined when 0% < Iout < 8%.
 2. The output current could drop down to 0% when dimming input is about 0Vdc or 10V PWM signal with 0% duty cycle.

I/P: 230 VAC


O/P: DIMMING TEST

Ta: 25°C

	Dimming voltage	0V	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V
1	Output Current	0A	0.035A	0.069A	0.103A	0.140A	0.175A	0.212A	0.248A	0.283A	0.318A	0.353A
	Percentage of rated current	0.00%	10.00%	19.71%	29.43%	40.00%	50.00%	60.57%	70.86%	80.86%	90.86%	100.86%
	Dimming Duty cycle	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
2	Output Current	0A	0.033A	0.068A	0.104A	0.140A	0.176A	0.211A	0.248A	0.283A	0.319A	0.354A
	Percentage of rated current	0.00%	9.43%	19.43%	29.71%	40.00%	50.29%	60.29%	70.86%	80.86%	91.14%	101.14%

TEST RESULT: OK

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~295VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	87V~295V
			I/P: (1)LOW-LINE-3V=87 V HIGH-LINE+10V=305 V O/P: FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230VAC ON: 0.5 Sec OFF: 0.5 Sec 20MIN (POWER ON/OFF NO DAMAGE)	TEST: OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P: 90 VAC ~295 VAC O/P: FULL~MIN LOAD Ta: 25°C	TEST: OK
3	AC CURRENT	0.4A/115VAC 0.16A/230VAC 0.13A/277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta: 25°C	I=0.227A/ 115VAC I=0.133A/ 230VAC I=0.116A/ 277VAC
4	LEAKAGE CURRENT	< 0.75mA / 277VAC	I/P: 277 VAC O/P: NO LOAD Ta: 25°C	L-CASE: 0.0034 mA N-CASE: 0.0037 mA
5	NO LOAD POWER CONSUMPTION	< 0.5W for Blank-Type < 1.2W for A-Type	I/P: 230VAC O/P: NO LOAD Ta: 25°C	0.378W for Blank-Type 0.5542W for A-Type
6	INRUSH CURRENT(Typ)	230V/ 30A Twidth =100 us measured at 50% Ipeak COLD START	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	I=4.14A/ 230VAC Twidth =31.2us
<p>INPUT=230VAC/50HZ @ FULL LOAD</p> <p>CH1: AC Input Voltage CH2: Input current</p>  <p>Ch2 最大 4.14 A</p> <p>37.8000µs</p>				
7	EFFICIENCY(Typ)	82%	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	84.44%

	<p>EFFICIENCY vs LOAD</p> <table border="1"> <caption>Efficiency vs Load Data</caption> <thead> <tr> <th>Load (%)</th> <th>277V Efficiency (%)</th> <th>230V Efficiency (%)</th> <th>115V Efficiency (%)</th> </tr> </thead> <tbody> <tr> <td>70%</td> <td>77.5</td> <td>80.0</td> <td>83.0</td> </tr> <tr> <td>80%</td> <td>79.5</td> <td>82.0</td> <td>84.5</td> </tr> <tr> <td>90%</td> <td>81.5</td> <td>83.5</td> <td>85.5</td> </tr> <tr> <td>100%</td> <td>82.5</td> <td>84.5</td> <td>86.0</td> </tr> </tbody> </table>			Load (%)	277V Efficiency (%)	230V Efficiency (%)	115V Efficiency (%)	70%	77.5	80.0	83.0	80%	79.5	82.0	84.5	90%	81.5	83.5	85.5	100%	82.5	84.5	86.0
Load (%)	277V Efficiency (%)	230V Efficiency (%)	115V Efficiency (%)																				
70%	77.5	80.0	83.0																				
80%	79.5	82.0	84.5																				
90%	81.5	83.5	85.5																				
100%	82.5	84.5	86.0																				
8	<p>POWER FACTOR</p>	<p>0.95/ 115VAC 0.92/ 230VAC 0.90/ 277VAC</p>	<p>I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta: 25°C</p>	<p>PF=0.992/ 115VAC PF=0.974/ 230VAC PF=0.9455/ 277VAC</p>																			
	<p>P.F vs LOAD</p> <table border="1"> <caption>P.F vs Load Data</caption> <thead> <tr> <th>Load (%)</th> <th>277V PF</th> <th>230V PF</th> <th>115V PF</th> </tr> </thead> <tbody> <tr> <td>70%</td> <td>0.92</td> <td>0.974</td> <td>0.992</td> </tr> <tr> <td>80%</td> <td>0.92</td> <td>0.974</td> <td>0.992</td> </tr> <tr> <td>90%</td> <td>0.92</td> <td>0.974</td> <td>0.992</td> </tr> <tr> <td>100%</td> <td>0.92</td> <td>0.974</td> <td>0.992</td> </tr> </tbody> </table>			Load (%)	277V PF	230V PF	115V PF	70%	0.92	0.974	0.992	80%	0.92	0.974	0.992	90%	0.92	0.974	0.992	100%	0.92	0.974	0.992
Load (%)	277V PF	230V PF	115V PF																				
70%	0.92	0.974	0.992																				
80%	0.92	0.974	0.992																				
90%	0.92	0.974	0.992																				
100%	0.92	0.974	0.992																				
9	<p>TOTAL HARMONIC DISTORTION</p>	<p>THD < 20% (@load ≥ 70% / 115VAC, 230VAC; @load ≥ 75% / 277VAC)</p>	<p>I/P: 115 VAC / 70% LOAD I/P: 230 VAC / 70% LOAD I/P: 277 VAC / 75% LOAD Ta: 25°C</p>	<p>THD=7.39% @70% load / 115VAC THD=11.60% @70% load / 230VAC THD=15.50% @75% load / 277VAC</p>																			
	<p>THD vs LOAD</p> <table border="1"> <caption>THD vs Load Data</caption> <thead> <tr> <th>Load (%)</th> <th>277V THD (%)</th> <th>230V THD (%)</th> <th>115V THD (%)</th> </tr> </thead> <tbody> <tr> <td>70%</td> <td>15.5</td> <td>11.6</td> <td>7.39</td> </tr> <tr> <td>80%</td> <td>14.5</td> <td>11.0</td> <td>7.0</td> </tr> <tr> <td>90%</td> <td>14.0</td> <td>10.8</td> <td>6.8</td> </tr> <tr> <td>100%</td> <td>13.5</td> <td>10.5</td> <td>9.5</td> </tr> </tbody> </table>			Load (%)	277V THD (%)	230V THD (%)	115V THD (%)	70%	15.5	11.6	7.39	80%	14.5	11.0	7.0	90%	14.0	10.8	6.8	100%	13.5	10.5	9.5
Load (%)	277V THD (%)	230V THD (%)	115V THD (%)																				
70%	15.5	11.6	7.39																				
80%	14.5	11.0	7.0																				
90%	14.0	10.8	6.8																				
100%	13.5	10.5	9.5																				

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	SHORT CIRCUIT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 90VAC I/P: 295VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Power Transistor	Q 1 Rated 7A/800V	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 550V (2) 532V (3) 546V
2	O/P Diode (MOSFET)	D100 Rated 5A/600V	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 514V (2) 510V (3) 512V
3	Control IC	U1 Rated 35V	I/P: High-Line +3V =298V O/P: (1) FULL LOAD (2) Output Short (3) Low Line No Load Ta: 25°C	(1) 14V (2) 11.1V (3) 14.1V
4	Clamp Diode	D 1 Rated 1A/1KV	I/P: High-Line +3V = 298V O/P: (1) Full Load input on/off (2) Output Short Ta: 25°C	(1) 518V (2) 524V

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P: 3.75KVAC/min	I/P-O/P: 4.2 KVAC/min Ta: 25°C	I/P-O/P: 1.744mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P: 500VDC>100MΩ	I/P-O/P: 500 VDC Ta: 25°C/70% RH	I/P-O/P: >9999MΩ

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS C	I/P: 230 VAC/50HZ O/P: FULL/70% LOAD Ta: 25°C	PASS
2	CONDUCTION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
3	RADIATION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
6	SURGE	EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
7	Test by certified Lab & Test Report Prepare			

■ **RELIABILITY TEST**

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																								
1	TEMPERATURE RISE TEST	MODEL: IDPC-25-350 1. ROOM AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 28.5℃ 2. HIGH AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 40.7℃																																																																										
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 38.5 ℃</th> <th>HIGH AMBIENT Ta=40.7 ℃</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>40.5℃</td><td>52.6℃</td></tr> <tr><td>2</td><td>L1</td><td>44.8℃</td><td>56.8℃</td></tr> <tr><td>3</td><td>BD1</td><td>53.0℃</td><td>64.5℃</td></tr> <tr><td>4</td><td>Q1</td><td>61.6℃</td><td>73.5℃</td></tr> <tr><td>5</td><td>C20</td><td>61.6℃</td><td>72.7℃</td></tr> <tr><td>6</td><td>U1</td><td>57.2℃</td><td>68.7℃</td></tr> <tr><td>7</td><td>D2</td><td>63.2℃</td><td>77.4℃</td></tr> <tr><td>8</td><td>T1</td><td>69.5℃</td><td>80.1℃</td></tr> <tr><td>9</td><td>D100</td><td>65.3℃</td><td>76.1℃</td></tr> <tr><td>10</td><td>Q100</td><td>62.7℃</td><td>73.7℃</td></tr> <tr><td>11</td><td>U100</td><td>67.0℃</td><td>77.8℃</td></tr> <tr><td>12</td><td>D200</td><td>64.7℃</td><td>75.5℃</td></tr> <tr><td>13</td><td>C201</td><td>57.0℃</td><td>68.8℃</td></tr> <tr><td>14</td><td>RG1</td><td>79.4℃</td><td>90.2℃</td></tr> <tr><td>15</td><td>L100</td><td>62.8℃</td><td>74.6℃</td></tr> <tr><td>16</td><td>C106</td><td>56.4℃</td><td>67.7℃</td></tr> <tr><td>17</td><td>LF100</td><td>55.3℃</td><td>66.8℃</td></tr> </tbody> </table>			NO	Position	ROOM AMBIENT Ta= 38.5 ℃	HIGH AMBIENT Ta=40.7 ℃	1	LF1	40.5℃	52.6℃	2	L1	44.8℃	56.8℃	3	BD1	53.0℃	64.5℃	4	Q1	61.6℃	73.5℃	5	C20	61.6℃	72.7℃	6	U1	57.2℃	68.7℃	7	D2	63.2℃	77.4℃	8	T1	69.5℃	80.1℃	9	D100	65.3℃	76.1℃	10	Q100	62.7℃	73.7℃	11	U100	67.0℃	77.8℃	12	D200	64.7℃	75.5℃	13	C201	57.0℃	68.8℃	14	RG1	79.4℃	90.2℃	15	L100	62.8℃	74.6℃	16	C106	56.4℃	67.7℃	17	LF100	55.3℃	66.8℃
NO	Position	ROOM AMBIENT Ta= 38.5 ℃	HIGH AMBIENT Ta=40.7 ℃																																																																									
1	LF1	40.5℃	52.6℃																																																																									
2	L1	44.8℃	56.8℃																																																																									
3	BD1	53.0℃	64.5℃																																																																									
4	Q1	61.6℃	73.5℃																																																																									
5	C20	61.6℃	72.7℃																																																																									
6	U1	57.2℃	68.7℃																																																																									
7	D2	63.2℃	77.4℃																																																																									
8	T1	69.5℃	80.1℃																																																																									
9	D100	65.3℃	76.1℃																																																																									
10	Q100	62.7℃	73.7℃																																																																									
11	U100	67.0℃	77.8℃																																																																									
12	D200	64.7℃	75.5℃																																																																									
13	C201	57.0℃	68.8℃																																																																									
14	RG1	79.4℃	90.2℃																																																																									
15	L100	62.8℃	74.6℃																																																																									
16	C106	56.4℃	67.7℃																																																																									
17	LF100	55.3℃	66.8℃																																																																									
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 295VAC/90VAC O/P: FULL/80% LOAD Ta= -25℃	TEST: OK																																																																								
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 ℃ NO DAMAGE	I/P: 305VAC O/P: FULL LOAD Ta=50 ℃ HUMIDITY= 95 %R.H	TEST: OK																																																																								
4	TEMPERATURE COEFFICIENT	±0.03 %/℃(0~50℃)	I/P: 230 VAC O/P: FULL LOAD	±0.0093%/℃																																																																								
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature: -45℃~ +85℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 5 CYCLE 5. Input/Output condition: AC OFF STATIC		TEST: OK																																																																								
6	THERMAL SHOCK TEST	1. Thermal shock Temperature: -25℃~ +55℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 16 CYCLE 5. Input/Output condition: 230VAC/Full Load AC ON/OFF TEST AC on 3 sec/AC off 1 sec TEST		TEST: OK																																																																								



7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency: 10~500Hz (3) Sweep Time: 10min/sweep cycle (4) Acceleration: 2G (5) Test Time: 60min in each axis (X.Y.Z) (6) Ta: 25°C	TEST: OK
8	CAPACITOR LIFE CYCLE	IDPC-25-350: SUPPOSE C106 IS THE MOST CRITICAL COMPONENT (1) I/P: 230VAC O/P: FULL LOAD Ta= 25 °C LIFE TIME (2) I/P: 230VAC O/P: FULL LOAD Ta= 50 °C LIFE TIME (3) I/P: 230VAC O/P: 75% LOAD Ta= 50 °C LIFE TIME	(1) 328204 HRS (2) 61721.3 HRS (3) 62290.9 HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 4394.6K hrs min. Telcordia SR-332 (Bellcore) ; 1093.3K hrs min. MIL-HDBK-217F (25°C)	
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30,000 hours @ Ta 50°C	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	CHENZH/ZHUOKB	SKY	LIUWY