



UK Declaration of Conformity

For the following equipment :

Product Name: Switching Power Supply

Model Designation:

NSP-75-xzzzz (x=5, 12, 15, 24, 27, 36, 48, 60 ; z=may be blank, -, 0~9, A~Z, a~z for market purpose)

NSP-100-xzzzz (x=5, 7.5, 12, 15, 24, 27, 36, 48, 60 ; z=may be blank, -, 0~9, A~Z, a~z for market purpose)

The designated product(s) is(are) in conformity with the relevant legislation:

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012: SI 2012 No. 3032

Electrical Equipment (Safety) Regulations 2016 :

BS EN 62368-1:2014+A11:2017

Dekra certificate No : 35-165219

Electrical Compatibility Regulations 2016 :

EMI (Electro-Magnetic Interference)

Conducted emission / Radiated emission

BS EN 55032:2015+A1:2020

Class B

Harmonic current

BS EN IEC 61000-3-2:2019+A1:2021+A2:2024

Voltage flicker

BS EN 61000-3-3:2013+A1:2019+A2:2021

EMS (Electro-Magnetic Susceptibility)

BS EN 55035:2017+A11:2020 BS EN IEC 61000-6-2:2019

ESD air

BS EN 61000-4-2:2009

Level 3 8KV

ESD contact

BS EN 61000-4-2:2009

Level 2 4KV

RF field susceptibility

BS EN IEC 61000-4-3:2020

Level 3 10V/m

EFT bursts

BS EN 61000-4-4: 2012

Level 3 2KV

Surge susceptibility

BS EN 61000-4-5:2014+A1:2017

Level 4 2KV/Line-Line

Surge susceptibility

BS EN 61000-4-5:2014+A1:2017

Level 4 4KV/Line-Earth

Conducted susceptibility

BS EN IEC 61000-4-6:2023

Level 3 10V

Magnetic field immunity

BS EN 61000-4-8:2010

Level 4 30A/m

Voltage dip, interruption

BS EN IEC 61000-4-11:2020

<5% residual voltage for 0.5 cycles, 70% residual voltage for 25 cycles ,
<5% residual voltage for 250 cycles

Note:

A component power supply with load will be installed into final equipment which consists of an electronically shielded metal enclosure. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Regulations on the complete installation again.

The EMC tests mentioned above are performed using a well defined metal plate to simulate said metal enclosure.

For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies". (as available on <http://www.meanwell.com>) and TDF (Technical Documentation File).

This Declaration is effective from serial number GC5xxxxxxx

Person responsible for marking this declaration :

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

(Manufacturer Address)

Eris Wu// Director, Group R&D :

(Name / Position)

Taiwan

(Place)

(Signature)

Sep. 29th, 2025

(Date)

Alex Tsai// Director, Product Strategy Center :

(Name / Position)

(Signature)