



Test Report : SGAS06x07

6W AC-DC High Reliable Extreme Small Wall-mounted Industrial Adaptor

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Other test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RIPPLE & NOISE	85mVp-p (Max)	I/P:230VAC O/P:FULL LOAD Ta:25°C	85 mVp-p
2	VOLTAGE TOLERANCE	-5% ~ +5% (Max)	I/P:90VAC~264VAC O/P:FULL~MIN. LOAD Ta:25°C	-0.43% ~ -0.11%
3	LINE REGULATION	-0.5% ~ +0.5% (Max)	I/P:90VAC ~264VAC O/P:FULL LOAD Ta:25°C	-0.05% ~ -0.20%
4	LOAD REGULATION	-5% ~ +5% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD Ta:25°C	+0.77% ~ +1.09%
5	SET UP TIME	1500 mS	I/P:230VAC O/P:FULL LOAD Ta:25°C	883.051 mS
6	RISE TIME	50 mS	I/P:230VAC O/P:FULL LOAD Ta:25°C	10.205 mS
7	HOLD UP TIME	5 mS (Min)	I/P:115VAC O/P:FULL LOAD Ta:25°C	22.674 mS

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	VOLTAGE RANGE	90VAC ~ 264VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	43V ~ 264V
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK
3	EFFICIENCY	77%	I/P:230VAC O/P:FULL LOAD Ta:25°C	77.03%
4	AVERAGE EFFICIENCY	78.88% (LEVEL VI) 79.03% (LEVEL 5)	I/P:115/230VAC O/P:25%、50%、75%、100% LOAD Ta:25°C	80.88% (115VAC) 79.12% (230VAC)
5	AC CURRENT	0.2A (Max)	I/P: 100VAC O/P:FULL LOAD Ta:25°C	0.133 A
6	NO LOAD POWER CONSUMPTION	< 0.1W (Max)	I/P:230VAC O/P: NO LOAD Ta:25°C	0.0695 W

7	INRUSH CURRENT	<50A COLD START	I/P:230VAC O/P:FULL LOAD Ta:25°C	32.703 A
8	LEAKAGE CURRENT	< 0.25mA	I/P:240VAC O/P:Min LOAD Ta:25°C	L-FG: 0.02mA N-FG: 0.02mA

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	105% ~ 180%	I/P:230VAC O/P:TESTING Ta:25°C	145.0% HICCUP MODE RESET : AUTO RECOVER
2	OVER VOLTAGE PROTECTION	>120%	I/P:230VAC O/P:MIN LOAD Ta:25°C	127.4% (MMSZ5239BF) Clamp by ZENER diode
3	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE RESET AUTO RECOVER

■ SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P:4242 VDC/min	I/P-O/P:4242 VDC/min Ta:25°C	I/P-O/P: 0.03uA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE

■ RELIABILITY TEST

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	MTBF	MIL-KDBK-217F NOTICES 2 PARTS COUNT TOTAL FAILURE RATE : 1.210625 M.T.B.F : 826001.20 HRS		

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG