



Test Report : SPRN01L-05

1W SIP Package DC-DC Regulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

Other

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-3.0 % ~ +3.0 % (Max)	I/P:5VDC O/P:FULL LOAD Ta:25°C	-1.14%	P
2	RIPPLE & NOISE	75 mVp-p (Max)	I/P:5VDC O/P:FULL LOAD Ta:25°C	10mV	P
3	LINE REGULATION	-1.0% ~ +1.0% (Max)	I/P:4.75VDC~5.5VDC O/P:FULL LOAD Ta:25°C	+0.03% ~ -0.11%	P
4	LOAD REGULATION	-1.0% ~ +1.0% (Max)	I/P:5VDC O/P:10% LOAD~FULL LOAD Ta:25°C	-0.19% ~ +0.19%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	4.75 VDC ~5.5 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	4.6VDC ~5.5VDC	P
2	EFFICIENCY	68% (Typ)	I/P:5VDC O/P:FULL LOAD Ta:25°C	68.39%	P
3	DC CURRENT	294 mA / FULL LOAD (Max) 35 mA / NO LOAD (Max)	I/P:5VDC O/P:NO / FULL LOAD Ta:25°C	289 mA / FULL LOAD 27.3 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	Current Limit Protection (60s max.)	I/P:5.5VDC O/P:FULL LOAD Ta:25°C	Current Limit Protection NO DAMAGE	P

SAFETY TEST
SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1.5K VDC/min	I/P-O/P:1.5K VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST
ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 8HRS I/P:5VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 8HRS I/P:5VDC O/P:FULL LOAD Ta=71°C 3. HIGH AMBIENT BURN-IN : 8HRS I/P:5VDC O/P:60% LOAD Ta=85°C			P										
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>52.5°C</td> <td>95.0°C</td> <td>101.9°C</td> </tr> </tbody> </table>			NO	Position	1	2	3	1	CASE	52.5°C	95.0°C	101.9°C	
NO	Position	1	2	3											
1	CASE	52.5°C	95.0°C	101.9°C											
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:5VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P										

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.80807 M.T.B.F : 1,237,522.68 HRS			P
TEST RESULT		TESTER		APPROVAL	
PASS		ARCHEN HSIAO		PETER CHENG	